The AS710R/AS850R is medium-sized ride-on scrubber dryers and the perfect solution for scrubbing and drying in heavy-trafic areas. Ideally suited for daily indoor cleaning in

mid-sized areas of railway stations, parking areas, shopping malls, exhibition centers, schools, hotels, public institutions and other commercial environments larger than 5000m<sup>2</sup>.

They are ideal for cleaning all kind off floors such as tiled floor, vinyl floor, sealed wood floor, marble, concrete etc.

AS710R/AS850R have modern styling and are compact, robust and easy to use. As standard, the machines are delivered with the following accessoiries: brush x 2, pad holder x 2, squeegee, on-board charger, and batteries  $6V \times 4$ . Front bumper and warning lamp is optional for the machine.

- Simple and easy to operate: Intuitive dashboard, one touch button and userfriendly menu for operation settings
- Robust and powerful: Use mechanical way to lift or lower the brush or squeegee. And the optional front bumper protects the machine for longer life-time
- Reliable and safety: Automatic reduce speed control and ergonomic
   Picture shown may not represent model quoted
   seat with safety switch. Built-in squeegee hanging system on recovery tank for easy machine transfer in narrow areas
- Storage for cell-phone or other gadgets, USB port provides a fast solution for charging your cell-phone
- An integrated on-board charger enables easy plug-in and battery charge at any outlet
- Large opening to the recovery tank allows easy cleaning

Standard equipment

	Included accessories	Ref. no.	Min. required	AS710R-EU RIDE-ON SCRUBBER 24V	AS710R-TR RIDE-ON SCRUBBER 24V	AS710R-US RIDE-ON SCRUBBER 24V
Pad Holder						
<b>(</b>	PAD HOLDER 355MM 14	VR14303	2	•	•	•
	PAD HOLDER 406MM 16"	VR19121	2			
Disc Brush						
0	BRUSH DISC 355MM 14 PPL	VR14300	2	•	•	•
	BRUSH PPL 406MM 16"	VR19120	2			
Deck Blade						



16708

	Included accessories	Ref. no.	Min. required	AS710R-EU RIDE-ON SCRUBBER 24V	AS710R-TR RIDE-ON SCRUBBER 24V	AS710R-US RIDE-ON SCRUBBER 24V
	BLADE SIDE SKIRT RUBBER KIT	VR14015	2	•	•	•
	BLADE SIDE SKIRT RUBBER KIT	VR19123	2			
Squeegee Bl	ade	1				
	BLADE SQUEEGEE FRONT PU 940MM 37	VR16002	1	•	•	•
	BLADE SQUEEGEE REAR PU 940MM 37	VR16003	1	•	•	•
	BLADE SQUEEGEE FRONT PU 1020MM 40	VF84207	0			
	BLADE SQUEEGEE REAR PU 1020MM 40	VF84208	0			
Battery		1				
	BATT.6V-198AH AGM C5	80565523	4	•	•	٠
On-Board Ch	arger	1				
	CHARGER ON BOARD KIT US	VR13442	1			•
Viper Access	ory					
۵.	CHARGER ON BOARD KIT EU	VR13240	1	•	•	
	KIT FRONT BUMPER	VR10027	1	•	•	•

Standard equipment

<ul> <li>Standard equipment</li> </ul>					1	1
	Included accessories	Ref. no.	Min. required	AS710R-CN RIDE-ON SCRUBBER NO BAT.	AS710R-NB RIDE-ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
Pad Holder						
<b>(</b>	PAD HOLDER 355MM 14	VR14303	2	•	•	
	PAD HOLDER 406MM 16"	VR19121	2			•
Disc Brush						
0	BRUSH DISC 355MM 14 PPL	VR14300	2	•	•	
	BRUSH PPL 406MM 16"	VR19120	2			•
Deck Blade		1			1	
1001	BLADE SIDE SKIRT RUBBER KIT	VR14015	2	•	•	
	BLADE SIDE SKIRT RUBBER KIT	VR19123	2			•
Squeegee Bla	ade	1			1	
	BLADE SQUEEGEE FRONT PU 940MM 37	VR16002	1	•	•	
	BLADE SQUEEGEE REAR PU 940MM 37	VR16003	1	•	•	
	BLADE SQUEEGEE FRONT PU 1020MM 40	VF84207	0			•
	BLADE SQUEEGEE REAR PU 1020MM 40	VF84208	0			•
Battery						

	Included accessories	Ref. no.	Min. required	AS710R-CN RIDE-ON SCRUBBER NO BAT.	AS710R-NB RIDE-ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
A A	BATT.6V-198AH AGM C5	80565523	4			
On-Board Ch	arger	'			•	
	CHARGER ON BOARD KIT US	VR13442	1			
Viper Access	ory					
	CHARGER ON BOARD KIT EU	VR13240	1	•	•	
	KIT FRONT BUMPER	VR10027	1	•	•	•

• Standard equipment

	Included accessories	Ref. no.	Min. required	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
Pad Holder					
<b>(</b>	PAD HOLDER 355MM 14	VR14303	2		
	PAD HOLDER 406MM 16"	VR19121	2	•	•
Disc Brush		·			
0	BRUSH DISC 355MM 14 PPL	VR14300	2		
	BRUSH PPL 406MM 16"	VR19120	2	•	•
Deck Blade					
1000	BLADE SIDE SKIRT RUBBER KIT	VR14015	2		
	BLADE SIDE SKIRT RUBBER KIT	VR19123	2	•	•
Squeegee Bla	ade				

	Included accessories	Ref. no.	Min. required	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
	BLADE SQUEEGEE FRONT PU 940MM 37	VR16002	1		
	BLADE SQUEEGEE REAR PU 940MM 37	VR16003	1		
	BLADE SQUEEGEE FRONT PU 1020MM 40	VF84207	0	•	•
	BLADE SQUEEGEE REAR PU 1020MM 40	VF84208	0	•	•
Battery					
1 - A	BATT.6V-198AH AGM C5	80565523	4		
On-Board Ch	arger				
	CHARGER ON BOARD KIT US	VR13442	1		•
Viper Access	ory				
	CHARGER ON BOARD KIT EU	VR13240	1		
	KIT FRONT BUMPER	VR10027	1	•	•
Model		AS710R-EU RIDE- ON SCRUBBER 24V	ON SCF	TR RIDE- AS RUBBER C 4V	710R-US RIDE- N SCRUBBER 24V
Ref. no.		50000315	5000	0317	50000318
PRODUCT F	EATURES				
Front and rea	r bumpers	•		•	•
Padholder inc	cluded	•		•	•
Battery charg	er	•		•	•
Battery version	on	•		•	•
Recovery em	ptying hoses	•		•	•

All information provided in this document is subject to change without prior notice

#### AS710R/AS850R

Model	AS710R-EU RIDE- ON SCRUBBER 24V	AS710R-TR RIDE- ON SCRUBBER 24V	AS710R-US RIDE- ON SCRUBBER 24V
Ref. no.	50000315	50000317	50000318
PRODUCT FEATURES			
Disc deck: 2 brushes	•	•	•
Water level indicator	•	•	•
Delivered ready to use (full package)	•	•	•
Onboard squeegee storage	•	•	•
Model	AS710R-CN RIDE- ON SCRUBBER NO BAT.	AS710R-NB RIDE- ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
Ref. no.	50000319	50000379	50000552
PRODUCT FEATURES			
Front and rear bumpers	•	•	•
Padholder included		•	•
Battery charger	•	•	
Battery version	•	•	•
Recovery emptying hoses	•	•	•
Disc deck: 2 brushes		•	•
Water level indicator	•	•	•
Delivered ready to use (full package)		•	
Onboard squeegee storage	•	•	•
Model		AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
Ref. no.		50000553	50000554
PRODUCT FEATURES			
Front and rear bumpers		•	•
Padholder included		•	•
Battery charger			
Battery version		•	•
Recovery emptying hoses		•	•
Disc deck: 2 brushes		•	•
Water level indicator		•	•
Delivered ready to use (full package)			
Onboard squeegee storage		•	•

#### AS710R/AS850R

Drive motor hp (W)500500500Brue motor holor (W)XX000XX00XX00XX00Vacuum motor power (W)0S00S00S00Battery type6/245Ah/C20 AGM4/245Ah/C20 AGM4/245Ah/C20 AGM4/245Ah/C20 AGMVacuum (mm H2O)18008001800Sound pressure level (dB(A))696969Productivity rate (m*h)4/413 ag mh4/413 ag mh4/413 ag mhCleaning with (mm)710mm710mm28inMa. sile tum (cm)10101010Solution tank (I)12012032galProductivity rate (m/h)262525Squeegee with (mm)365 x 2355 x 271 lobSolution tank (I)12012032galDrive whoels (cm)353577 lobBrush geneed (RPM)264204204Duran speed (RPM)204204204Darnersions, L x W x H (mm)1800x780x12301800x780x1230Brush geneed (kPM)22522771 lobAus speed (kPM)26424V 25A24V 25AAus speed (kPM)2824V 25A24V 25ACharging system24V 25A24V 25A24V 25AAus speed (kPM)60m60m60m60mAus speed (kPM)25252525Charging system24V 25A24V 25A24V 25ACharging system24W 25A24V 25A24V 25ACharging sys	Technical specifications	AS710R-EU RIDE- ON SCRUBBER 24V	AS710R-TR RIDE- ON SCRUBBER 24V	AS710R-US RIDE- ON SCRUBBER 24V
Vacuum motor power (M)         500         500         500           Battery type         6V 245 APC20 AGM         7V 7V           Clear in minimized (m/h)         100         10	Drive motor hp (W)	500	500	500
Battery type         6V 245AhC20 AGM 4PCS         6V 245AhC20 AGM 4PCS         6V 245AhC20 AGM 4PCS           Vacuum (mm H2O)         1800         1800         1800           Sound pressure level (dB(A))         69         69         69           Productivity rate (m?h)         4413 sq m/h         4413 sq m/h         4413 sq m/h           Clearing width (mm)         710mm         710mm         28in           Min. aisle turn (cm)         177,3         177,3         177,3           Max. clinbing rate (%)         10         10         32gal           Recovery tark (l)         120         120         32gal           Drive wheels (cm)         25         25         25           Squeegee width (mm)         940         940         37in           Brush pressure (kg)         304         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         1730x810x1410         1580x760x120	Brush motor (W)	2X300	2X300	2X300
Battery type         4PCS         4PCS         4PCS         4PCS         4PCS           Vacuum (mm H2O)         1800         1800         1800           Sound pressure level (dB(A))         69         69         69           Productivity rate (m7h)         4413 sq mAh         4413 sq mAh         4413 sq mAh           Cleaning width (mm)         710mm         710mm         28in           Mix. aisle turn (cm)         177,3         177,3         177,3           Max. clinbing rate (%)         10         10         10           Solution tank (I)         120         120         32gal           Prove wheek (cm)         25         25         25           Squeegee width (mm)         940         940         37in           Brush pressure (kg)         355 x 2         355 x 2         14in x 2           Brush pressure (kg)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         1730x810x1410         1580x760x130         16machine)           Brush pressure (kg)         240         244         244         244         244         244         244         244         244         244         244         244         244         244	Vacuum motor power (W)	500	500	500
Sound pressure level (dB(A))         69         69         69           Productivity rate (m <sup>7</sup> )h)         4413 sq m/h         4413 sq m/h         4413 sq m/h         4413 sq m/h           Cleaning width (mm)         710mm         710mm         710mm         28in           Min. aisle tum (cm)         177,3         177,3         177,3         177,3           Max. climbing rate (%)         10         10         10         32gal           Soluto tank (l)         20         22         32gal           Recovery tank (l)         20         22         32gal           Drive wheels (cm)         35         25         25           Squeegee widh (mm)         440         940         37n           Brush finester (nm)         355 x 2         355 x 2         14in x2           Brush pressure (kg)         35         35         77 lb           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1580x760x1230         1580x760x1230         1580x760x1230           Batery compartment size (L x W x H (mm)         610x408x365         610x408x365         610x408x365           Ass.spipping weight         435         435         950lb           Asseed (km/	Battery type			
Productivity rate (m <sup>2</sup> )h         4413 sq m/h         4413 sq m/h         4413 sq m/h           Cleaning width (mm)         710mm         710mm         710mm         28in           Min. aisle turn (cm)         177,3         177,3         177,3         177,3           Max. climbing rate (%)         10         10         10         10           Solution tank (l)         120         32gal         32gal           Recovery tank (l)         20         25         25         25           Squeegee widh (mm)         4940         940         37n           Brush diameter (mm)         355 x 2         355 x 2         14in x2           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         1700x810x1410         1580x760x1230         1580x760x1230           Brush speed (RPM)         225         225         771.6 lb         1580x760x1230         1580x760x1280         1580x760x1280         1580x760x1280         1580x760x1280	Vacuum (mm H2O)	1800	1800	1800
Cleaning width (mm)         710mm         710mm         710mm         28in           Min. aisle turn (cm)         177,3         177,3         177,3         177,3           Max. climbing rate (%)         10         10         10         32gal           Recovery tank (l)         120         120         32gal           Price wheels (cm)         25         25         25           Squeegee width (nm)         940         940         37in           Brush presure (kg)         35         35         77 lb           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         (B8.11 x 31.89 x (package)         (B8.11 x 31.89 x (package)           Brush speed (RPM)         204         204         204         204           Dimensions, L x W x H (mm)         1500x760x1230         (machine)         (B8.11 x 31.89 x (package)         (B8.11 x 31.89 x (package)         55.51 (package)         65.51 (package)         65.51 (package)         (B8.11 x 31.89 x (package)         55.51 (package)         (B6	Sound pressure level (dB(A))	69	69	69
Min. aisie turn (cm)         177,3         177,3         177,3           Max. cimbing rate (%)         10         10         10           Solution tank (l)         120         120         32gal           Recovery tank (l)         120         120         32gal           Drive wheels (cm)         25         25         25           Squeegee width (mm)         940         940         37in           Brush pressure (kg)         35         35         77 lb           Brush pressure (kg)         36         35         35           Brush pressure (kg)         1730x810x1410         (86.11 x 31.89 x (Beckage)         66.11 x 31.89 x (Beckage)           Dimensions, L x W x H (mm)         1730x810x1410         68.11 x 31.89 x (Beckage)         1580x760x1230         1580x760x1230         1580x760x1230           Length x width x height (mm)         610x408x365         610x408x365         24x16x14.3 in         160x408x365         24x16x14.3 in           Net weight (kg)         225         225         771.6 ib         1580x760x1230         1580x760x1230         1580x760x1230         1580x760x1230         1580x760x1230         1580x760x1230         1580x760x1230         24x16x14.3 in         Net weight (kg)         242         242         242         24x16x14.	Productivity rate (m <sup>2</sup> /h)	4413 sq m/h	4413 sq m/h	4413 sq m/h
Max. climbing rule (%)         10         10         10           Solution tank (I)         120         120         32gal           Recovery tank (I)         120         120         32gal           Drive wheels (cm)         25         25         25           Squeegee width (mm)         940         940         37in           Brush diameter (mm)         355 x 2         355 x 2         14in x2           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1580x760x1230         1780x810x41410         1780x810x4140           Brush speed (RPM)         610x408x365         610x408x369         255.16 (package)           Length x width x height (mm)         610x408x365         1880x760x1230           Battery compartment size (L x W x H) (mm)         610x408x365         610x408x365         24x15x41.31           Net weight (kg)         225         225         771.6 Ib           Max. shipping weight         435         435         959Ib           Charging system         24V 25A         24V 25A         24V 25A           Max. speed (km/h)         6km/h         6km/h         3.7 mph           Technical specifications         Sono         Sono         Sono	Cleaning width (mm)	710mm	710mm	28in
Solution tank (f)         120         120         32gal           Recovery tank (f)         120         120         32gal           Drive wheels (cm)         25         25         25           Squeegee width (mm)         940         940         37in           Brush diameter (mm)         355 x 2         14in x2           Brush pressure (kg)         35         35         77 lb           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         (package)         1580x760x1230         1500x760x1230         1500x760x1230	Min. aisle turn (cm)	177,3	177,3	177,3
Recovery the (i)         120         120         32gal           Drive wheels (cm)         25         25         25           Squeegee width (nm)         940         940         37in           Brush diameter (mm)         355 x 2         355 x 2         14in x2           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410 (package)         1580x760x1230 (machine)         1580x760x120 (machine)	Max. climbing rate (%)	10	10	10
Drive wheels (cm)         25         25           Squeegee width (mm)         940         940         37in           Brush diameter (mm)         355 x 2         355 x 2         14in x 2           Brush pressure (kg)         35         35         5         77 lb           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         1730x810x1410         855.5in (package)           Length x width x height (mm)         1580x760x1230         1580x760x1230         1580x760x1230           Battery compartment size (L x W x H) (mm)         610x409x365         610x409x365         24x16x14.3 in 89.x           Max. shipping weight         435         435         259lb           Charging system         24V 25A         24V 25A         24V 25A           Ass. speed (km/h)         6km/h         3.7mph           Technical specifications         S500         500         500           Brush motor (W)         500         500         500           Yeacuum motor power (W)         500         500         500           Battery type         1800         1800         1800           Yeacuum (mH2O)         1800         1800         1800	Solution tank (I)	120	120	32gal
Squeege with mm)         940         940         37in           Brush diameter (mm)         355 x 2         355 x 2         14in x 2           Brush pressure (kg)         35         35         77 lb           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410         1730x810x1410         68.11 x 31.89 x           Length x width x height (mm)         1880x760x1230         1580x760x1230         1580x760x1230           Battery compartment size (L x W x H) (mm)         610x409x365         610x408x365         24x16x14.3 in           Net weight (kg)         225         27         771.6 lb           Max. shipping weight         435         435         959lb           Charging system         24V 25A         24V 25A         24V 25A           Max. speed (km/h)         6km/h         6km/h         3.7m,h           Pre-chnical specifications         S510R-CN RIDEs         SSSOR-EU RIDER           No SCRUBERE NO         SASTOR-NN RIDE         SSSOR-SEL RIDER           Vacuum motor p(W)         S00         S00         S00           Battery type         500         S00         S00         S00           Gracuum (mH ZO)         1800         1800	Recovery tank (I)	120	120	32gal
Brush diameter (mm)         355 x 2         355 x 2         14in x2           Brush pressure (kg)         35         35         77 lb           Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410 (package)         68,11 x 31.89 x (package)         68,11 x 31.89 x (package)           Length x width x height (mm)         1580x760x1230 (machine)         1580x760x1230 (machine) <td>Drive wheels (cm)</td> <td>25</td> <td>25</td> <td>25</td>	Drive wheels (cm)	25	25	25
Brush pressure (kg)3537 loBrush speed (RPM)204204Dimensions, L x W x H (mm)1730x810x1410 (package)1730x810x1410 (package)68.11 x 31.89 x (s5.5in (package)Length x width x height (mm)1580x760x1230 (machine)1580x760x1230 (machine)1680x760x1230 (machine)Battery compartment size (L x W x H) (mm)610x408x365610x408x36524x16x14.3 in (machine)Net weight (kg)225225771.6 lb 3435Max. shipping weight435435350Charging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7 mphTechnical specificationsSono500500Drive motor hp (W)500500500Battery type500500500Parkery type500500500Parkery type610245Ah/C20AGH 4PCS24X30LVacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m <sup>2</sup> /h)4413 sq m/h5130	Squeegee width (mm)	940	940	37in
Brush speed (RPM)         204         204         204           Dimensions, L x W x H (mm)         1730x810x1410 (package)         1730x810x1410 (package)         68.11 x 31.89 x (package)         55.51n (package)           Length x width x height (mm)         1580x760x1230 (machine)         1580x760x1230 (machine)         1580x760x1230 (machine)         1580x760x1230           Battery compartment size (L x W x H) (mm)         610x408x365         610x408x365         24x16x14,3 in           Net weight (kg)         225         225         771.6 ib           Max. shipping weight         435         435         959lb           Charging system         24V 25A         24V 25A         24V 25A           Max. speed (km/h)         6km/h         6km/h         3.7mph           Technical specifications         S500         500         500           Drive motor hp (W)         500         500         500           Battery type         500         500         500           Battery type         6V 245Ah/C20 AGM         6V245Ah/C20 AGM         2400           Vacuum (mm H20)         1800         1800         1800         1800           Sound pressure level (dB(A))         69         69         69         69           Productivity rate (m <sup>2</sup> /h)<	Brush diameter (mm)	355 x 2	355 x 2	14in x2
Dimensions, L x W x H (mm)1730x810x1410 (package)1730x810x1410 (package)1730x810x1410 (package)168.11 x 31.89 x 55.5in (package)Length x width x height (mm)1580x760x1230 (machine)1580x760x1230 (machine)1580x760x1230 (machine)1580x760x1230 (machine)Battery compartment size (L x W x H) (mm)610x408x365610x408x36524x16x14,3 inNet weight (kg)225225771.6 lbMax. shipping weight435435959lbCharging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsS500500500Drive motor hp (W)500500500Battery typeS00500500Battery type6V 245Ah/C20 AGM 4PCS4PCSVacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sg m/h413 sg m/h5130	Brush pressure (kg)	35	35	77 lb
Diffensions, L x w x H (htm)(package)(package)(package)(s5.5in (package)Length x width x height (mm)1580x760x1230 (machine)1580x760x1230 (machine)1580x760x1230 (machine)1580x760x1230 (machine)1580x760x1230 (machine)Battery compartment size (L x W x H) (mm)610x408x365610x408x36524x16x14,3 inNet weight (kg)225225771.6 lbMax. shipping weight435435959lbCharging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsAS710R-CN RIDE ON SCRUBBER NO BATTAS710R-NB RIDE ON SCRUBBER NO BATTERYAS850R-EU RIDER NO BATTERY NO BATTERYDrive motor hp (W)500500500Battery type500500500Battery type6V 245Ah/C20 AGM 4PCS4PCSVacuum (mm H2O)18001800Sound pressure level (dB(A))6969Productivity rate (m²/h)4413 sg m/h4413 sg m/h	Brush speed (RPM)	204	204	204
Length X width X neight (mm)(machine)(machine)(machine)(machine)Battery compartment size (L x W x H) (mm)610x408x365610x408x36524x16x14.3 inNet weight (kg)225225771.6 lbMax. shipping weight435435959lbCharging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsS710R-NB RDE SATTERYS500S00Drive motor hp (W)500500500Brush motor (W)200200200Vacuum motor power (W)500500500Battery type60245Ah/C20 AGM 4PCS18001800Vacuum (mm H2O)180018001800Sound pressure level (dB(A))6413 sq m/h441 sq m/h5130	Dimensions, L x W x H (mm)			
Net weight (kg)225225771.6 lbMax. shipping weight435435959lbCharging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsAS710R-CN RIDE ON SCRUBER NOSS710R-NB RDE BATTERYAS850R-EU RIDER CHARGERDrive motor hp (W)500500500Brush motor (W)2X3002X3002x300Vacuum motor power (W)500500500Battery type6V 245Ah/C20 AGM 4PCS6V 245Ah/C20 AGM 4PCS1800Vacuum (m H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sq m/h413 sq m/h5130	Length x width x height (mm)			
Max. shipping weight435435959lbCharging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsAS710R-CN RIDE NON SRATERY NON BATTERY NON BAT	Battery compartment size (L x W x H) (mm)	610x408x365	610x408x365	24x16x14,3 in
Charging system24V 25A24V 25A24V 25AMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsAS710R-CN RIDE on SCRUBBER NoSAS70R-NB RIDE on SCRUBBER NoSAS850R-EU RIDER NO SCRUBBER NODrive motor hp (W)500500500Brush motor (W)2X3002X3002X300Vacuum motor power (W)500500500Battery type6V 245Ah/C20 AGN 4PCS6V 245Ah/C20 AGN 4PCS1800Vacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sq m/h5130	Net weight (kg)	225	225	771.6 lb
Max. speed (km/h)6km/h6km/h3.7mphMax. speed (km/h)6km/h6km/h3.7mphTechnical specificationsAS710R-CN RIDE ON SCRUBBER NO DN SCRUBBER NO ON SCRUBBER NO ON SCRUBBER NO DN SCRUBBER NO DN SCRUBBER NO DN SCRUBBER NO ON SCRUBBER NO DN SCRUBER NO DN SCRUBBER NO DN SCRUBER NO D	Max. shipping weight	435	435	959lb
AS710R-CN RIDE ON SCRUBBER NOAS710R-NB RIDE ON SCRUBBER NOAS880R-EU RIDER NO BATTERY NO CHARGERDrive motor hp (W)500500500Brush motor (W)5002X3002X300Vacuum motor power (W)500500500Battery type6V 245Ah/C20 AGM 4PCS6V 245Ah/C20 AGM 4PCS1800Vacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sq m/h5130	Charging system	24V 25A	24V 25A	24V 25A
Technical specificationsON SCRUBBER NO BATTERYNO BATTERY NO CHARGERDrive motor hp (W)500500500Brush motor (W)2X3002X3002x300Vacuum motor power (W)500500500Battery type6V 245Ah/C20 AGM 4PCS6V 245Ah/C20 AGM 4PCS1800Vacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sq m/h5130	Max. speed (km/h)	6km/h	6km/h	3.7mph
Brush motor (W)2X3002X3002x300Vacuum motor power (W)500500500Battery type $6V 245Ah/C20 AGM \ 4PCS$ $6V 245Ah/C20 AGM \ 4PCS$ 1800Vacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sq m/h5130	Technical specifications	ON SCRUBBER NO	ON SCRUBBER NO	NO BATTERY NO
Vacuum motor power (W)500500Battery type $6V 245Ah/C20 AGM 4PCS$ $4V 245Ah/C20 AGM 4PCS$ Vacuum (mm H2O)180018001800Sound pressure level (dB(A))696969Productivity rate (m²/h)4413 sq m/h5130	Drive motor hp (W)	500	500	500
Battery type         6V 245Ah/C20 AGM 4PCS         6V 245Ah/C20 AGM 4PCS           Vacuum (mm H2O)         1800         1800         1800           Sound pressure level (dB(A))         69         69         69           Productivity rate (m²/h)         4413 sq m/h         5130	Brush motor (W)	2X300	2X300	2x300
Battery type         4PCS         4PCS           Vacuum (mm H2O)         1800         1800           Sound pressure level (dB(A))         69         69           Productivity rate (m²/h)         4413 sq m/h         5130	Vacuum motor power (W)	500	500	500
Sound pressure level (dB(A))         69         69           Productivity rate (m²/h)         4413 sq m/h         5130	Battery type			
Productivity rate (m²/h)         4413 sq m/h         4413 sq m/h         5130	Vacuum (mm H2O)	1800	1800	1800
	Sound pressure level (dB(A))	69	69	69
Cleaning width (mm)         710mm         710mm         810	Productivity rate (m <sup>2</sup> /h)	4413 sq m/h	4413 sq m/h	5130
	Cleaning width (mm)	710mm	710mm	810

Technical specifications	AS710R-CN RIDE- ON SCRUBBER NO BAT.	AS710R-NB RIDE- ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
Min. aisle turn (cm)	177,3	177,3	182,5
Max. climbing rate (%)	10	10	10
Solution tank (I)	120	120	120
Recovery tank (I)	120	120	120
Drive wheels (cm)	25	25	25
Squeegee width (mm)	940	940	1060
Brush diameter (mm)	355 x 2	355 x 2	406 x 2
Brush pressure (kg)	35	35	40
Brush speed (RPM)	204	204	204
Dimensions, L x W x H (mm)	1730x810x1410 (package)	1730x810x1410 (package)	1580x890x1230
Length x width x height (mm)	1580x760x1230 (machine)	1580x760x1230 (machine)	1580x890x1230
Battery compartment size (L x W x H) (mm)	610x408x365	610x408x365	610x408x365
Net weight (kg)	225	225	230
Max. shipping weight	435	435	440
Charging system	24V 25A	24V 25A	
Max. speed (km/h)	6km/h	6km/h	6
Technical specifications		AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
Drive motor hp (W)		500	0.67hp
Brush motor (W)		2x300	2X0.4hp
Vacuum motor power (W)		500	0.67hp
Battery type			
Vacuum (mm H2O)		1800	1800
Sound pressure level (dB(A))		69	69
Productivity rate (m <sup>2</sup> /h)		5130	55219 ft²/h
Cleaning width (mm)		810	31.8in
Min. aisle turn (cm)		182,5	182,5
Max. climbing rate (%)		10	10
Solution tank (I)		120	32gal
Recovery tank (I)		120	32gal
Drive wheels (cm)		25	9.8in
Squeegee width (mm)		1060	41.7in
Brush diameter (mm)		406 x 2	16in x2
Brush pressure (kg)		40	88 lb
Brush speed (RPM)		204	204

Technical specifications	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
Dimensions, L x W x H (mm)	1580x890x1230	62.2x35x48.48 inch
Length x width x height (mm)	1580x890x1230	62.2x35x48.48 inch
Battery compartment size (L x W x H) (mm)	610x408x365	24x16x14,3 inch24x16x14,3 in
Net weight (kg)	230	507 lbs
Max. shipping weight	440	970lbs
Charging system		
Max. speed (km/h)	6	3.7mph

 $\bullet$  Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	AS710R-EU RIDE-ON SCRUBBER 24V	AS710R-TR RIDE-ON SCRUBBER 24V	AS710R-US RIDE-ON SCRUBBER 24V	
External Char	External Charger						
8	CHARGER HF 24V 25A SB120R	80542425	0				
8	CHARGER HF 24V 25A SB175R	80542426	1	0	0		
Battery							
A CAR	BATT.6V-198AH AGM C5	80565523	4	٠	•	•	
	BATT. 6V-180AH GEL MONOBLOC	80564000	4				
FT 05 200 FT 05 200 Experimental FT 05 200 FT 05 700 FT	BATT. 6V-200AH WET TUBULAR MONOBLOC	80563200	4				
Squeegee Bla	ade						
	BLADE SQUEEGEE FRONT LINATEX 940MM 37	VR16002L	1	0	0	0	
	BLADE SQUEEGEE FRONT PU 940MM 37	VR16002	1	•	•	•	

	Accessories	Ref. no.	Min. required	AS710R-EU RIDE-ON SCRUBBER 24V	AS710R-TR RIDE-ON SCRUBBER 24V	AS710R-US RIDE-ON SCRUBBER 24V
	BLADE SQUEEGEE REAR LINATEX 940MM 37	VR16003L	1	0	0	0
	BLADE SQUEEGEE REAR PU 940MM 37	VR16003	1	•	•	•
	BLADE SQUEEGEE FRONT PU 1020MM 40	VF84207	0			
	BLADE SQUEEGEE FRONT RED GUM 1020MM 40	VF84207L	0			
	BLADE SQUEEGEE REAR PU 1020MM 40	VF84208	0			
	BLADE SQUEEGEE REAR RED GUM 1020MM 40	VF84208L	0			
Viper Accesso	ory					
	CHARGER ON BOARD KIT EU	VR13240	1	•	•	
	KIT FRONT BUMPER	VR10027	1	•	•	•
	KIT WARNING LIGHT	VR17160	1			
Deck Blade						
11111	BLADE SIDE SKIRT RUBBER KIT	VR14015	2	•	•	•
	BLADE SIDE SKIRT RUBBER KIT	VR19123	2			
Disc Brush						

	Accessories	Ref. no.	Min. required	AS710R-EU RIDE-ON SCRUBBER 24V	AS710R-TR RIDE-ON SCRUBBER 24V	AS710R-US RIDE-ON SCRUBBER 24V
0	BRUSH DISC 13INCH MID GRIT 0.9MM BLUE	VR14307	2	0	0	0
0	BRUSH DISC 355MM 14 PPL	VR14300	2	•	•	•
	BRUSH PPL 406MM 16"	VR19120	2			
Pad Holder						
۲	PAD HOLDER 355MM 14	VR14303	2	•	•	•
	PAD HOLDER 406MM 16"	VR19121	2			
On-Board Cha	arger					
	CHARGER ON BOARD KIT US	VR13442	1			•
Accessory Kit						
	BATTERY TRAY	VR10048	0	0	0	0
Battery and C	Charger					
DRY CELL	BATT.6V-222AH AGM MONOBLOC	80566222	0			
Other						
	SEAT BELT KIT 1.3M	VR41537	1			
Light Option						
X	BLUE LIGHT KIT	55943344	1			

ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	AS710R-CN RIDE-ON SCRUBBER NO BAT.	AS710R-NB RIDE-ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
External Char	ger					
8	CHARGER HF 24V 25A SB120R	80542425	0			0
8	CHARGER HF 24V 25A SB175R	80542426	1		0	0
Battery						
	BATT.6V-198AH AGM C5	80565523	4			
	BATT. 6V-180AH GEL MONOBLOC	80564000	4			
	BATT. 6V-200AH WET TUBULAR MONOBLOC	80563200	4			
Squeegee Bla	ade					
	BLADE SQUEEGEE FRONT LINATEX 940MM 37	VR16002L	1			
	BLADE SQUEEGEE FRONT PU 940MM 37	VR16002	1	•	•	
	BLADE SQUEEGEE REAR LINATEX 940MM 37	VR16003L	1			
	BLADE SQUEEGEE REAR PU 940MM 37	VR16003	1	•	•	
	BLADE SQUEEGEE FRONT PU 1020MM 40	VF84207	0			•

	Accessories	Ref. no.	Min. required	AS710R-CN RIDE-ON SCRUBBER NO BAT.	AS710R-NB RIDE-ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
	BLADE SQUEEGEE FRONT RED GUM 1020MM 40	VF84207L	0			0
	BLADE SQUEEGEE REAR PU 1020MM 40	VF84208	0			•
	BLADE SQUEEGEE REAR RED GUM 1020MM 40	VF84208L	0			0
Viper Accesso	ory					
	CHARGER ON BOARD KIT EU	VR13240	1	•	•	
	KIT FRONT BUMPER	VR10027	1	•	•	•
	KIT WARNING LIGHT	VR17160	1	0	0	0
Deck Blade			1			
3000	BLADE SIDE SKIRT RUBBER KIT	VR14015	2	•	•	
	BLADE SIDE SKIRT RUBBER KIT	VR19123	2			•
Disc Brush						
0	BRUSH DISC 13INCH MID GRIT 0.9MM BLUE	VR14307	2			
0	BRUSH DISC 355MM 14 PPL	VR14300	2	•	•	
	BRUSH PPL 406MM 16"	VR19120	2			•
Pad Holder						

	Accessories	Ref. no.	Min. required	AS710R-CN RIDE-ON SCRUBBER NO BAT.	AS710R-NB RIDE-ON SCRUBBER NO BATTERY	AS850R-EU RIDER NO BATTERY NO CHARGER
۲	PAD HOLDER 355MM 14	VR14303	2	•	•	
	PAD HOLDER 406MM 16"	VR19121	2			•
On-Board Cha	arger					
	CHARGER ON BOARD KIT US	VR13442	1			
Accessory Kit						
	BATTERY TRAY	VR10048	0	0	0	0
Battery and C	harger					
DRY CELL	BATT.6V-222AH AGM MONOBLOC	80566222	0			0
Other		1				
<u></u>	SEAT BELT KIT 1.3M	VR41537	1			
Light Option						
N.	BLUE LIGHT KIT	55943344	1			
<ul> <li>Standard equipment</li> </ul>	, <sup>O</sup> Supplementary accessories, <sup>□</sup> Mountable equipment					

Battery					
8	CHARGER HF 24V 25A SB175R	80542426	1	0	
8	CHARGER HF 24V 25A SB120R	80542425	0	0	
External Cha	rger				
	Accessories	Ref. no.	Min. required	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER

	Accessories	Ref. no.	Min. required	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
	BATT.6V-198AH AGM C5	80565523	4		
	BATT. 6V-180AH GEL MONOBLOC	80564000	4		
FI do 200 Exercision Representation PD 000 PD 000 P	BATT. 6V-200AH WET TUBULAR MONOBLOC	80563200	4	0	
Squeegee Bla	de				
	BLADE SQUEEGEE FRONT LINATEX 940MM 37	VR16002L	1		
	BLADE SQUEEGEE FRONT PU 940MM 37	VR16002	1		
	BLADE SQUEEGEE REAR LINATEX 940MM 37	VR16003L	1		
	BLADE SQUEEGEE REAR PU 940MM 37	VR16003	1		
	BLADE SQUEEGEE FRONT PU 1020MM 40	VF84207	0	•	•
	BLADE SQUEEGEE FRONT RED GUM 1020MM 40	VF84207L	0	O	0
	BLADE SQUEEGEE REAR PU 1020MM 40	VF84208	0	•	•
	BLADE SQUEEGEE REAR RED GUM 1020MM 40	VF84208L	0	0	0
Viper Accesso	ry				

	Accessories	Ref. no.	Min. required	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER
	CHARGER ON BOARD KIT EU	VR13240	1		
	KIT FRONT BUMPER	VR10027	1	•	•
	KIT WARNING LIGHT	VR17160	1	0	0
Deck Blade					
IIIII	BLADE SIDE SKIRT RUBBER KIT	VR14015	2		
	BLADE SIDE SKIRT RUBBER KIT	VR19123	2	•	•
Disc Brush					
0	BRUSH DISC 13INCH MID GRIT 0.9MM BLUE	VR14307	2		
0	BRUSH DISC 355MM 14 PPL	VR14300	2		
	BRUSH PPL 406MM 16"	VR19120	2	•	•
Pad Holder					
	PAD HOLDER 355MM 14	VR14303	2		
	PAD HOLDER 406MM 16"	VR19121	2	•	•
On-Board Cha	arger				
	CHARGER ON BOARD KIT US	VR13442	1		•
Accessory Kit					
	BATTERY TRAY	VR10048	0	0	0

	Accessories	Ref. no.	Min. required	AS850R-TR RIDER NO BATTERY NO CHARGER	AS850R-US RIDER NO BATTERY WITH CHARGER	
Battery and C	Charger					
DRY CELL	BATT.6V-222AH AGM MONOBLOC	80566222	0	0		
Other						
<b>***</b> >	SEAT BELT KIT 1.3M	VR41537	1			
Light Option	Light Option					
X	BLUE LIGHT KIT	55943344	1			