

ACQUA FREDDA - DUE RUOTE

Serie K 2000



Fig.: K 2160 TST





		K 2160 TS	K 2160 TST	K 2195 TS	K 2195 TST	K 2175 TS	K 2175 TST
		senza avvolgitubo	incl. avvolgitubo	senza avvolgitubo	incl. avvolgitubo	senza avvolgitubo	incl. avvolgitubo
Dati tecnici							
Pressione di servizio regolabile	bar / MPa	30-140 / 3-14	30-140 / 3-14	30-180 / 3-18	30-180 / 3-18	30-160 / 3-16	30-160 / 3-16
Pressione massima	bar / MPa	160 / 16	160 / 16	195 / 19.5	195 / 19.5	175 / 17.5	175 / 17.5
Potenza di allacciamento elettrico	V / ~ / Hz / A	230 / 1 / 50 / 14	230 / 1 / 50 / 14	230 / 1 / 50 / 14	230 / 1 / 50 / 14	400 / 3 / 50 / 6.7	400 / 3 / 50 / 6.7
Giri Motore	g/min	1400	1400	1400	1400	1400	1400
Portata d'acqua	l/min l/h	11 660	11 660	8 480	8 480	12 720	12 720
Potenza nominale / Potenza erogata	kW kW	3.2 2.4	3.2 2.4	3.2 2.4	3.2 2.4	3.3 2.6	3.3 2.6
Cavo di allacciamento alla rete	m	5	5	5	5	5	5
Dimensioni (l x l x a)	mm	375 / 360 / 900	375 / 360 / 900	375 / 360 / 900	375 / 360 / 900	375 / 360 / 900	375 / 360 / 900
Peso	kg	37	39.5	37	39.5	37	39.5
Aspirazione di detergenti		●	●	●	●	●	●
Accessori in dotazione							
Avvolgitubo		—	●	—	●	—	●
Tubo flessibile ad alta pressione in tessuto d'acciaio	m	10	15	10	15	10	15
Pistola ad arresto automatico	Modello	M2000	M2000	M2000	M2000	M2000	M2000
Lance con ugello ammazzasporco	Dimensioni ugello	● 042	● 042	○ 03	○ 03	● 042	● 042
Lancia con ugello Vario-Jet	Dimensioni ugello	● 042	● 042	○ 03	○ 03	● 042	● 042

